





For panel-specific information, see page 49.



1" Convex PC System 1" Concave PC System



CURVED FIELD-LOK™

SKU: FLX (convex, min. radius 8'-0" aluminum, 12'-0" steel)

MATERIAL

.032 aluminum

24, 22* ga. metallic coated steel

24 ga. 55% Al-Zn alloy coated steel with acrylic coating

16, 20 oz. copper*

PANEL SPECS

Coverage: 1" seam - 131/2", 171/2", 213/4"

1½" seam - 12½", 16½", 20¾" | Custom widths available

Minimum Length: 4'-0" Seam Height: 1", 11/2"

AVAILABLE

Dome (1" seam height only)

TEXTURE

Smooth

MINIMUM SLOPE

2:12 depending on climate conditions

www.atas.com/curvedfieldlok

CURVED PC™ SYSTEM

SKU: PCX (convex, minimum radius 2'-9"), PCV (concave, minimum radius 4'-0")

MATERIAL

.032, .040 aluminum

24 ga. metallic coated steel

24 ga. 55% Al-Zn alloy coated steel with acrylic coating

16 oz. copper*

PANEL SPECS

Coverage: 11¼", 125%", 145%"**, 15¼" **Copper and Dark Bronze Anodized only

Minimum Length: 3'-0" Seam Height: 1"

AVAILABLE

Tapered, Dome

TEXTURE

Smooth or Stucco Embossed

MINIMUM SLOPE

3:12

www.atas.com/curvedpc